

EuroStar^{SL+}

Proven Performance Meets Innovation



TOP OF THE CLASS UL AIRCRAFT WITH SALES SUCCESS IN 50 COUNTRIES

- Certified quality from EASA approved manufacturer
- Low empty weight meeting the strictest UL regulations
- Comfortable cockpit providing 1,18 m shoulder room
- Excellent reliability proven in flight schools worldwide
- Popular among sport pilots and flight instructors
- Globally guaranteed spare parts support

EuroStar^{SL+}



Technical data

SPECIFICATION

Wing span	8.15 m
Wing area	9.84 m ²
Length	5.98 m
Cabin width	1.18 m
Empty weight EuroStar SL+	288 kg
Empty weight EuroStar SL	276 kg
MTOW	472 kg
Design load factors	+6 / -3
Glide ratio	1:10
Fuel tank capacity EuroStar SL+	120 l
Fuel tank capacity EuroStar SL	65 l / 78 l (opt.)

Engine – Rotax 912 ULS (100 hp) / TBO 2000 hrs

PERFORMANCE

Never exceed speed	270 km / h
Maximum level speed	240 km / h
Cruising speed	200 km / h
Stall speed	65 km / h
Rate of climb	1400 ft / min
Service ceiling	6000 m
Take off run	100 m
Landing run	210 m
Average fuel consumption	14 l / h
Range EuroStar SL+	1300 km
Range EuroStar SL	750 km / 920 (opt.)
Endurance EuroStar SL+	8 hours

Under ISA conditions. All information can be changed without prior notice.

Certified for the towing of gliders up to 700 kg MTOW and banners up to 140 sq.m.



EVEKTOR-AEROTECHNIK
Letecká 1384, 686 04 Kunovice, Czech Republic
Phone: +420 572 537 317; Fax: +420 572 537 910
E-mail: sales@evektor.com, www.evektor.com

Dealer in your area: